

Commander Jr. Call Control System



Commander Jr.

The Commander Jr. Call Control System from Science Dynamics Corporation (SciDyn) is a powerful tool to help small correctional facilities manage and control inmate telephone calls.

Commander Jr. provides a wide array of editable call control capabilities, advanced call monitoring and integrated voice recording. The system features SciDyn's patented 3-way call detection technology with 36 tunable parameters that continually scan the call path end-to-end and reduce the potential of fraudulent activities.

The built-in AdminManager application provides system administrators with real-time access to call databases and call detail records from each networked location. Every Commander Jr manages 4 or 8 lines and is fully compatible with SciDyn's larger scale Commander I and Commander II systems for multiple facility call control service.

SciDyn has been providing call control solutions since 1986 and is now serving thousands of inmate phone lines nationwide. Please contact us for more information at 856-424-0068 or sales@scidyn.com.

Standard Features:

- Manages 4 or 8 lines per chassis
- Patented 3-way call detection
- Cut-off keys for phone service shutdown
- Personal Identification Numbers (PINs)
- Remote diagnostics
- Detailed system operation logs and reports
- Customized announcements
- Multiple language support
- Automated operator services
- Tiered security access control
- Positive DTMF call acceptance

- Flexible telephone service scheduling
- Call limits by usage and frequency
- Allowed destination numbers by PIN
- Call allow tables
- Call restriction tables
- Remote called party blocking
- Call duration timing
- Free call capabilities
- Programmable speed dialing
- Detailed call records
- Customizable billing formats

Optional Features:

- Integrated voice recording
- Blended debit/collect calling
- Live call monitoring
- Line concentration
- Prepaid Calling Cards



Commander Jr Specification Sheet

Dimensions

23.9 (W) x 1.7 (H) x 23.7 (D) inches

Power

- 95 to 135V AC or 180 to 270 VAC
- 250 (Watts) Maximum

Operating Environment

- Temperature: 10° to 40° C
- Humidity 10 to 90% non-condensing

Base System

The Commander Jr. can be purchased with 4 or 8 lines.

Network Options

SciDyn's Commander Jr, Commander I and Commander II chassis are fully compatible and can be networked together to provide statewide and multiple facility call control service.

Software

BubbleLINK® Software Architecture



CORPORATE HEADQUARTERS

Science Dynamics Corporation

2059 Springdale Road, Suite 100

Cherry Hill, NJ 08003 USA

Tel: 1-856-424-0068 • Fax: 1-856-751-7361

E-mail: sales@scidyn.com

Traded on OTCBB (SIDY.OB)